



# **TECHNICAL DATA SHEET**

## **DPDAC/DPDACM 9mm**

Description	Profile series with diamond cross-section 45°
Reference	DPDAC 965 - DPDAC 980 - DPDACM 911
Material	Aluminium
Surface	Powder coated
Color	RAL 0006500 Concrete grey RAL 0808005 Sand RAL 9011 Black Matt
Length cm/inches	250/300 - 98,4252/118,11
High mm/inches	9 / 0,3543
Weight	0,151 kg/m
Accessories	Internal corner (-YI) and External Corner (Y)
Picture	5,86 /0,23 5,86 /0,23 5,86 /0,23 9/0,35 10/0,39



DPDAC 965 DPDAC 980 DPDACM 911





## **TECHNICAL DATA SHEET**

#### **Powder-coated aluminium**

This involves powder coating of aluminium usual a special process. This is harder and stronger than other finishes. It is resistant to UV light as well as chemicals and weathering. Visible surfaces may be susceptible to scratches. Use only cleaning agents that do not scour.

### **Note**

The suitability for use in terms of mechanical and chemical resistance must always be checked in each individual case. When installing and grouting our metal profiles, the adhesive and grouting materials must be removed immediately with clean water and a soft sponge to prevent damage due to corrosion of the profile. Do not use acidic (e.g. cement fog remover) or alkaline cleaning agents in combination with all metal profiles. Clean with clean water and wipe with a dry linen cloth.