



TECHNICAL DATA SHEET

DPA

| Description | Edge trim for walls and floors |
|---------------|--|
| Reference | DPA 70 – DPA 90 – DPA 110 – DPA 125 – DPA 150 *– DPA 200 * (* discontinued item) |
| Material | Aluminium |
| Surface | Natural |
| Color | Silver |
| Length | 250 cm |
| High | 7-9-11-12,5-15-20 mm |
| Visible width | 8 mm |
| Accessories | Internal and external corner (-Y) |
| Picture | |











TECHNICAL DATA SHEET

<u>Aluminium</u>

Aluminium provides a medium degree of mechanical strength. It is sensitive to alkaline materials, e.g. fresh cement can cause bad staining (oxidation marks). Adhesive and grout should always be removed immediately from all visible surfaces using plenty of water. Once oxidation marks have been allowed to appear, it is practically impossible to remove them. High air humidity levels during the joint drying phase can increase this effect.

Note

The suitability for use in terms of mechanical and chemical resistance must always be checked in each individual case. When installing and grouting our metal profiles, the adhesive and grouting materials must be removed immediately with clean water and a soft sponge to prevent damage due to corrosion of the profile. Do not use acidic (e.g. cement fog remover) or alkaline cleaning agents in combination with all metal profiles. Clean with clean water and wipe with a dry linen cloth.

09/10/2023